

you can
Canon

i-SENSYS
MF4350d

Laser Mono
Multifunctional Printer

Compact, complete and
productive laser All-in-One

i-SENSYS MF4350d

Benefit from professional print, fax, copy and scan quality - with automatic document feeding to boost productivity. This compact and complete mono laser All-in-One is fast, energy efficient, easy to use and features automatic double-sided printing.



22ppm
monochrome
printing

250-sheet
paper tray

Virtually zero
warm-up time

1200 x 600dpi
print resolution

9600 x 9600dpi
Colour scanning

Duplex
printing



WHAT'S IN THE BOX

Main unit, cartridge FX10, power cable, USB cable, telephone line cable, starter guide, manuals on CD, user software CD, warranty card.

KEY FEATURES

- Compact laser All-in-One: print, fax, copy and scan
- 22 ppm mono printing and copying
- No waiting with Quick First-Print technologies
- First Copy Out Time of 9 seconds or less
- Automatic double-sided printing
- Up to 1200 x 600 dpi print resolution
- Colour scanning: up to 9600 x 9600 dpi, save as PDF
- Super G3 fax with 256-page memory*
- 35-sheet Automatic Document feeder
- 250-sheet paper tray
- Energy saving - only 3 watts in sleep mode
- Maintenance-free All-in-One Cartridge for continuous high quality output
- USB 2.0 Hi-speed interface

* Based on ITU-T Standard Chart No. 1

DIMENSIONS (W x D x H)

390 x 432 x 455 mm

SUPPORTED OS

Windows 2000/ XP/ Vista

Mac OS X version 10.2.8-10.5.x (Web distribution only)

Linux (Web distribution only & English print driver only)



PRINT



COPY




FAX



SCAN

i-SENSYS MF4350d



- 1 Flatbed and ADF
- 2 250-sheet tray
- 3 Optional telephone handset
- 4 FX10 cartridge

Specifications

Machine type Available functions	Mono Laser All-in-One Print, Copy, Scan and Fax
PRINTER Print speed Printing method Print quality Print resolution Double sided printing Printer languages Print margins Toner saver mode	Up to 22 ppm (A4) Monochrome laser beam printing Up to 1200 x 600 dpi with Automatic Image Refinement 600 x 600 dpi Automatic UFRII-LT 6 mm-top and bottom, 5 mm-left and right Yes
COPIER Copy speed First Copy Output Time (FCOT) Copy resolution Copy modes Double sided copying Multiple copy Reduction / Enlargement Toner saver mode Other features	Up to 22 cpm (A4) Approx. 9 seconds or less Up to 600 x 600 dpi Text, Text/Photo, Text/Photo+, Photo 1-sided to 2-sided (Manual) Up to 99 copies 50-200% in 1% increments Yes Collate, 2 on 1
SCANNER Type Scan resolution Colour scanning depth Greyscales Compatibility Max. scan width	Colour Optical: Up to 600 x 1200 dpi Enhanced: Up to 9600 x 9600 dpi 24 bit/24 bit (input/output) 256 levels TWAIN, WIA 216 mm
FAX Modem speed Receive mode Fax resolution Fax memory Speed dials Group dials/destinations Sequential broadcast Memory backup Double sided faxing Other features	Super G3 33.6kbps (Up to 3 seconds/page ¹) Fax only, Fax/Tel Auto Switch, Answer Mode, Manual Standard: 200 x 100 dpi Fine: 200 x 200 dpi Photo: 200 x 200 dpi Super fine: 200 x 400 dpi Up to 256 pages ¹ Max. 107 (including 7 one-touch dials) Max. 8 dials/ Max.50 destinations Max. 123 locations 5 mins Yes (Receive/ Transmit (Manual)) Fax Forwarding, Dual Access, Remote Reception, PC Fax (TX only)
MEDIA HANDLING Scanner type Paper input (Standard) Paper output Media types	Flatbed and Automatic Document Feeder (ADF) 250-sheets tray 1-sheet manual feed slot 35-sheets ADF 100-sheets Plain paper, Heavy paper, Recycled paper, Transparency, Label, Envelope

Media sizes	Tray: A4, B5, A5, Executive, Envelope (COM10, Monarch, DL, ISO-C5), LTR, LGL, Custom sizes: Width 76 x 127 mm; Length 216 x 356 mm Manual feed slot: A4, B5, A5, Executive, Envelope (COM10, Monarch, DL, ISO-C5), LTR, LGL, Custom sizes: Width 76 x 127 mm; Length 216 x 356 mm ADF: A4, A5, Legal, Letter, Custom (W x L): Max 216 x 356 mm Min 105 x 148.5 mm Tray: 64 to 128 g/m ² Manual feed slot: 64 to 163 g/m ² ADF: 40 to 105 g/m ²
Media weights	Tray: 64 to 128 g/m ² Manual feed slot: 64 to 163 g/m ² ADF: 40 to 105 g/m ²
INTERFACE & SOFTWARE Interface type Operating System compatibility Software and printer management	USB 2.0 Hi-speed Windows 2000/ XP/ Vista Mac OS X version 10.2.8-10.5.x ² Linux ³ Omni Page SE, Presto! Page Manager, MF toolbox
GENERAL FEATURES Duty cycle Warm-up Time Memory Control panel Dimensions with trays (W x D x H) Installation space (W x D x H) Weight Operating environment Power Source Power Consumption Noise Levels	Max. 10,000 pages per month Approx. 10 seconds from power on 32 MB (shared) 16 characters x 2 lines backlit LCD 390 mm x 432 mm x 455 mm 390 mm x 813 mm x 588 mm Approx. 12.75 Kg Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation) 220-240 V (±10%), 50/60 Hz (±2 Hz) Maximum: Approx. less than 650 W Active: Approx. less than 650 W Standby: Approx. less than 9 W Sleep mode: Approx. 3 W Typical Electricity Consumption (TEC): 1.039 kWh/week Sound Pressure ⁴ Active: 63.5 dB(A) or less Standby: Inaudible
CONSUMABLES Cartridges	Cartridge FX10 (2,000 pages ⁵)
ACCESSORIES/ OPTIONS Items	Network connectivity using AXIS 1650 Print Server Telephone 6 Kit

All specifications subject to change without notice

¹ Based on ITU-T Standard Chart No. 1

² Web distribution only

³ English print driver only

⁴ Declared noise emission in accordance with ISO 9296

⁵ Based on 5% coverage



you can
Canon

Canon Inc.
www.canon.com

Canon Europa N.V.
www.canon-europe.com

English-UK Edition
© Canon Europa N.V., 2008 (0908)

Canon (UK) Ltd
Woodhatch
Reigate
Surrey
RH2 8BF
Telephone No: 01737 220000
Facsimile No: 01737 220022
www.canon.co.uk

Canon Ireland
Arena Road,
Sandyford Industrial Estate
Dublin 18, Ireland
T: 01 2052400
F: 01 2958141
www.canon.ie