Ideal for enterprise, small office and residential application

1xWAN,1xLAN,1xFXS,1xPSTN lifeline



Yealink SIP-GW3CM is a next generation IP communication solution with complete functions and high performance-price ratio. It is a voice, fax, internet data and PSTN "all-in-one" integrated access device, enabling feature-rich telephone services and features over internet connection.

Its elegant and fashionable design, high-level voice quality, 3 SIP accounts availability can bring customers unlimited convenience and content of IP communication.



Analog Telephone Adaptor

SIP-GW3CM

Network Protocol

SIP v1(RFC2543), v2(RFC3261)
IP/TCP/UDP/RTP/RTCP/SDP
IP/ICMP/ARP/RARP/SNTP
TFTP Client/DHCP Client/PPPoE Client

Telnet/HTTP Server

DNS Client

NAT/DHCP Server

ToS field

Voice Feasture

G.711, G.723.1, G.726 G.729A, G.729B VAD, CNG, LEC Packet Loss Compensation Adaptive Jitter Buffer

SIP Server

Registrar Server: 3 SIP account Outbound Proxy

Configuration

Web Browser Console/Telnet Keypad Auto-Provision

Firmware Upgrade

TFTP Console HTTP Auto-Provision

Call Function

Call Hold
Call Waiting
Call Transfer
Call Forward
Caller ID
3-way conference

Phone Function

Volume Adjustment Speed dial key Phone Book Redial Flash

Dial Method

Direct IP call without SIP proxy
Dial number via SIP server
Dial URL via SIP Server

DTMF Function

In-Band DTMF
Out-of-Band DTMF
SIP Info

IP Assignment

Static IP DHCP PPPoE

NAT Traversal

STUN UPnP

Security

HTTP 1.1 basic/digest authentication for Web setup MD5 for SIP authentication (RFC 2069/RCF 2617)

Physical Features

1xFXS port, 1xPSTN lifeline
Power adaptor:Input:AC 100~240V
Output:DC 12V/0.5A
Product:130x80x28MM
Operating humidity:10~95%
LED:Status,PSTN,VoIP
Storage temperature:Up to 60 C
Carton Meas:470x450x168MM
N.W/CTN:9.3Kg
G.W/CTN:9.9Kg
Oty/CTN:20pcs

Interface:2xRJ45 10/100M Base-T

Certifications





