
# microTALK\*

# Two-Way Radio Model MT 600



1. Antenna

2. External Speaker/

- Microphone/Charge Jack
- 3. Mode/Power Button
- 5. Channel Select Buttons
- 6. Speaker/Microphone
- 7. Light/Max Range Button
- 8. Volume Control Buttons
- 10. Call Button
- 12. Battery Compartment
- 13. Lock Tab

13



#### Features

# • Two-Way Radio

with up to a 5 km (3 mile) range

- 8 Channels\*
- 38 CTCSS Privacy Codes
- 83 DCS Privacy Codes
- Backlit LCD Display
- Battery Saver Circuitry
- Maximum Range Extender
- Call Alert (5 selectable tones)
   Scan (Channel, Privacy Codes)
- Vox Mode for Hands-Free Operation
- Auto Squelch
- Selectable On/Off "Roger Beep" Confirmation Tone
- Key Lock
- External Speaker/Microphone/Charge Jack
- Belt Clip

\*You are not allowed to use channels 1 and 2 in France.
This situation can change; please contact the French radio licensing authority for more information.

- Scan Rogy DCS VOX CTCSS
  Power Saver 7
  - 1. Scan Icon
    - . Roger Been Icon
- 3. DCS Icon
- 4. Lock Icon
- 5. VOX Icon
  6 CTCSS Icon

- 7. Battery Low Icon
  - . Privacy Code Numbers
- 9. Power Saver Icon
- 10. Main Channel Number
- 11. Receive/Transmit Icon

# Product Information

This microTALK® radio has been manufactured to meet all required standards for radio equipment using PMR 446 frequencies as authorized. The use of this two-way radio product involves the public airways and its use may be subject to local lows or regulations. Contact your radio licensing authority for more information.

# Carina for Your Radio

Your microTALK® radio will give you years of trouble-free service if cared for properly. Here are a few suggestions:


- Handle the radio gently.
- Keep it away from dust.
- Never put the radio in water or in a damp place.
- Avoid exposure to extreme temperatures.

### Charger and Rechargeable Batteries

#### To Insert Ratteries in Radio:

- 1. Remove belt clip by releasing belt clip latch and sliding clip up.
- 2. Push up on lock tab to remove battery cover.
- 3. Insert batteries according to polarity markings.

NOTE: Estimated operation time on full charge: 12 hours.



WARNING: Do not put batteries into fire or expose to high heat. They may explode.



# For Charaina Cobra's microTALK® Radio(s):

- 1. Check to see that the batteries have been inserted properly. See above for battery installation instructions.
- 2. Insert round connector of wall charger into the charge inck located at the top of the radio. The wall charger has two (2) round connectors which enables you to charge either one (1) or two (2) radios at a time.
- 3. Plug the wall charger into electrical outlet.



It is not recommended to recharge batteries more than 24 hours. Estimated operation time on a full charge is 12 hours. Use only the supplied rechargeable batteries and wall charger for recharging your Cobra microTALK® radio. Non-rechargeable alkaline batteries can also be used.

#### Radio Power

### To Turn Your Radio On:

- Press and hold the MODE/POWER button until you hear a series of audible tones indicating that the radio is On. Your microTALK® radio is now in LISTENING MODE, ready to receive transmissions. The radio is always in LISTENING MODE. except when the TALK, CALL or MODE/POWER buttons are pressed.



- Press and hold the MODE/POWER button for two (2) seconds.

#### **Battery Low Indicator**

When battery power is low, the BATTERY LOW indicator will blink, indicating that batteries should be recharged or replaced.

WARNING: Only the supplied NiMH batteries can be recharged.

# **Battery/Power Saver**

If there are no transmissions within 10 seconds, the unit will automatically switch to Battery Save mode and POWER SAVER will appear in the display. This will not affect the unit's ability to receive incoming transmissions.















# Communicating with Another Person

- 1 Press and hold the TALK hutton
- 2. With the microphone about 5 cm (2 inches) from your mouth, speak in a normal voice.
- 3. Release the button when you have finished talking and listen for a response.

You cannot receive incoming calls while pressing the TALK button.

NOTF: Both radios must be tuned to the same channel and privacy code to communicate.



- Release the TALK button to receive incoming transmissions. Your microTALK® is always in LISTENING MODE while the TALK or CALL buttons are not pressed.





# To Adjust Volume

- Press the VOLLIME LIP or the VOLLIME DOWN buttons

A dual beep sound is used to indicate that you have reached the minimum (1) or maximum (8) volume level.



# Call Button

Press and release the CALL button.

The other person will hear a two (2) second ringing tone. You cannot send or receive transmissions during the two (2) second call tone

NOTE: Both radios must be tuned to the same channel and privacy code to communicate.







#### To Select a Channel

- With the radio on, select any of the eight (8) channels by pushing the CHANNEL UP or CHANNEL DOWN hutton

You can press and hold the CHANNEL UP or CHANNEL DOWN button for fast advance.

NOTE: Both radios must be tuned to the same channel and privacy code (see "CTCSS Privacy Codes" or "DCS Privacy Codes") to communicate.

# **Lock Function**

The LOCK button locks the CHANNEL UP. CHANNEL DOWN and MODE/POWER buttons to prevent accidental operation.

# To Use the Lock Function:

- Press and hold the LOCK button for two (2) seconds to turn the Lock On or Off

A double beep sound is used to confirm your Lock On or Off request. When the radio is in Lock Mode. the Lock icon will be displayed.







### To Illuminate Display

- Press and release the LIGHT/MAX RANGE button to illuminate the display for 10 seconds.

# Auto Squelch/Maximum Range Extender

Your microTALK® radio is equipped with Auto Squelch, which automatically shuts off weak transmissions and unwanted noise resulting from terrain, conditions or from reaching your maximum range limit.

You can temporarily turn Off Auto Squelch or turn On Maximum Range Extender, allowing all signals to be received and extending the maximum range of your radio.



#### To Temporarily Turn Off Auto Sauelch:

- Press the LIGHT/MAX RANGE button for less than five (5) seconds.

If you hear two (2) beeps, you have turned the Maximum Range Extender On (see below).

# To Turn Maximum Range Extender On:

- Press and hold the LIGHT/MAX RANGE button for at least five (5) seconds until you hear two (2) beeps. indicating that the Maximum Range Extender is On.

# To Turn Maximum Range Extender Off:

- Press and release the LIGHT/MAX RANGE button or change channels.

### microTALK® Range

Your microTALK® radio has a range of up to 5 kilometres (3 miles). Your range will vary depending on terrain and conditions.

In flat, open country, your radio will operate at maximum range. Buildings and foliage in the path of the signal can reduce the range.


Dense foliage and hilly terrain will further reduce the signal.

Remember, you can achieve maximum range by using Maximum Range Extender. See above for details.



External Speaker/Microphone/Charge Jack

To Attach the External Speaker/Microphone or Charger:









Your microTALK® radio can be fitted with an optional external speaker/microphone (not included), freeing your hands for other tasks

Insert the plug into the iack.

### Scrolling Through the Mode Functions

By scrolling through the Mode Functions, you will be able to select or change preferred features of your microTALK® radio. While you are scrolling through the Mode Functions, your radio features will be displayed in the same gredetermined order:

Set CTCSS Privacy Codes

Set DCS Privacy Codes Set VOX On/Off

Set VOX Sensitivity Level

Set Channel Scan

Set CTCSS Privacy Code Scan

Set DCS Privacy Code Scan Set Call Tones

Set "Roger Beep" On/Off


# CTCSS Privacy Codes

CTCSS (Continuous Tone Coded Squelch System) is an advanced tone coding system allowing you to select one of 38 privacy codes to reduce incomina transmissions from other users on the channel.

NOTE: If you are using a privacy code, both radios must be tuned to the same channel and privacy code to communicate. Each channel will remember the last privacy code you selected.

#### To Select a CTCSS Privacy Code:

 After selecting a channel, press and release the MODE button until the CTCSS iron flashes on the display. In addition to the CTCSS iron, either OFF or the small numbers next to the channel number will flash on the display.



- 3. When your desired privacy code is displayed, choose one of the following:
  - a. Press the MODE button to enter the new setting and proceed to other functions.
    - b. Press the LOCK button to enter the new setting and return to LISTENING MODE.
  - c. Do not press any buttons for 15 seconds to enter the new setting and return to LISTENING MODE







# **DCS Privacy Codes**

DCS (Digital Coded Squelch) is an advanced digital coding system allowing you to select one of 83 privacy codes to reduce incoming transmissions from other users on the channel.

NOTE: If you are using a DCS code, both radios must be turned to the same channel and DCS privacy code to communicate. Each channel will remember the last code you selected.

### To Select a DCS Privacy Code:

- 1. After selecting a channel, press and release the MODE button until the DCS icon flashes on the display. In addition to the DCS icon, either OFF or the small numbers next to the channel number will flash on the display.
- 2. If DCS and OFF are flashing, press the CHANNEL UP or CHANNEL DOWN button to exit OFF and proceed to select a privacy code; or, if DCS and the small numbers next to the channel number are flashing, press the CHANNEL UP or CHANNEL DOWN button to select a privacy code.
- 3. When your desired privacy code is displayed, choose one of the following:
  - a. Press the MODE button to enter the new setting and proceed to other functions.
    - b. Press the LOCK button to enter the new setting and return to LISTENING MODE.
    - c. Do not press any buttons for 15 seconds to enter the new setting and return to LISTENING MODE.









Voice Activated Transmit (VOX)

In VOX Mode, your microTALK® radio can be used "hands-free," automatically transmitting when you speak. You can set the VOX sensitivity level to fit the volume of your voice and avoid transmissions triggered by background noise.

#### To Turn VOX Mode On or Off:

- 1. Press the MODE button until the VOX icon flashes on the display. The current On or Off setting is displayed.
- 2. Press the CHANNEL UP or CHANNEL DOWN button to turn VOX On or Off.
- 3. When your desired VOX Mode setting is displayed, choose one of the following:
  - a. Press the MODE button to enter the new setting and proceed to other functions.
  - b. Press the LOCK button to enter the new setting and return to LISTENING MODE.
  - c. Do not press any buttons for 15 seconds to enter the new setting and return to LISTENING MODE.







# MODE FUNCTIONS OPERATION

English







# To Set the VOX Sensitivity Level:

- 1. Press the MODF button until the VOX icon flashes and the current sensitivity. level is displayed.
- The current sensitivity level is displayed with the letter "L" and a number 1 to 5. 5 being the most sensitive level and 1 being the least sensitive level.
- 2. Press the CHANNEL UP or CHANNEL DOWN button to change the setting.
- 3. When your desired VOX sensitivity level is displayed, choose one of the following:
  - a. Press the MODE button to enter the new setting and proceed to other functions.
  - b. Press the LOCK button to enter the new setting and return to LISTENING MODE.
  - c. Do not press any buttons for 15 seconds to enter the new setting and return to LISTENING MODE.

# Channel Scan

Your microTALK® radio can automatically scan channels (1 to 8).

NOTE: The radio janores specific CTCSS or DCS privacy codes while scanning channels.

#### To Scan Channels:

Press the MODE button until the Scan icon and the channel number flash on the display.

2. Press the CHANNEL UP or CHANNEL DOWN button to begin scanning channels.

The Scan icon will continue to be displayed when channel scan is On. Your radio will continue to scan all channels and stop if an incomina transmission is detected. Your radio will remain on that channel for 10 seconds. While setting channel scan, if you do not press any buttons for 15 seconds, your radio will automatically

return to LISTENING MODE on the channel or channel/privacy code displayed before you entered Mode Functions.





- a Press and hold the TALK button to communicate on that channel. Your radio will remain on that channel and return to LISTENING MODE
  - b. Press the CHANNEL UP or CHANNEL DOWN button to resume scanning channels.

If you press the TALK button while scanning and not within 10 seconds of receiving a transmission, you will transmit on the channel on which you last received a transmission. This will return the radio to LISTENING MODE.

If you do not press any button within 10 seconds, your radio will automatically resume scanning channels.

# During Scanning (while not receiving a transmission), You Can Choose From The Following:

- a. Press and hold the TALK button to communicate on either the channel or channel/privacy code that was displayed before you entered Mode Functions or the channel on which, during scanning, you last received a transmission. This will return the radio to LISTENING MODE.
- b. Press the MODE button to proceed to set privacy code on the channel that was either displayed before you entered Mode Functions or on which, during scanning, you last received a transmission (see "CTCSS Privacy Code Scan" or "DCS Privacy Code Scan" for further details).
- c. Press the LOCK button to return to LISTENING MODE on either the channel or channel/privacy code that was displayed before you entered Mode Functions or the channel on which, during scanning, you last transmitted or received.

# Som Rog)

elect Scan Privacy



Channel Buttons

# CTCSS Privacy Code Scan

Your microTALK® radio can automatically scan the CTCSS privacy codes (01 to 38) within one (1) channel

## To Scan Privacy Codes:

- While in LISTENING MODE, press the CHANNEL UP or CHANNEL DOWN button to choose the channel on which you wish to scan the CTCSS privacy codes.
   Press the MODE button until the Scan icon. CTCSS icon and the small numbers flash on the disalar.
- Press the CHANNEL UP or CHANNEL DOWN button to begin scanning CTCSS privacy codes within the
- Press the CHANNEL UP or CHANNEL DOWN button to begin scanning CICSS privacy codes within the channel you selected.

The Scan icon will continue to be displayed when CTCSS privacy code scan is On. Your radio will continue to scan CTCSS privacy codes and stop as an incoming transmission is detected. Your radio will remain on that

channel/privacy code for 10 seconds.

While setting CTCSS grivacy code scan, if you do not gress any buttons for 15 seconds, your radio will automatically return to LISTENING MODE on

the channel/privacy code that was displayed before you entered Mode Functions.

# During An Incoming Transmission, You Can Choose From The Following:

- a. Press and hold the TALK button to communicate on that channel/privacy code. Your radio will remain on that channel/privacy code and return to LISTENING MODE.
- b. Press the CHANNEL UP or CHANNEL DOWN button to resume scanning CTCSS privacy codes.

If you press the TALK button while scanning and not within 10 seconds of receiving a transmission, you will transmit on the channel/privacy code on which you last received a transmission. This will return the radio to LISTENING MODE.

If you do not press any button within 10 seconds, your radio will automatically resume scanning CTCSS privacy codes.

### During Scanning (while not receiving a transmission), You Can Choose From The Following:

- Press and hold the TALK button to communicate on either the channel or channel/privacy code that was displayed before you entered Mode Functions or channel/privacy code on which, during scanning, you lost received a transmission. This will return the radio to LISTENING MANNE
- b. Press the MODE button to proceed to next available Mode Function.
- c. Press the LOCK button to return to LISTENING MODE on either the channel or channel/privacy code that was displayed before you entered Mode Functions or the channel/privacy code on which, during scanning, you lost received a transmission.

# DCS Privacy Code Scan

You can automatically scan the DCS privacy codes (01 to 83) within one channel.

NOTE: The radio must be in the CTCSS OFF MODE when scrolling through mode functions or DCS mode will be skipped.

# To Scan DCS Privacy Codes:

- 1. While in the LISTENING MODE, press the CHANNEL UP or CHANNEL DOWN button to choose the channel on which you wish to scan the DCS privacy codes.
- 2. Press the MODE button until the SCAN icon. DCS icon and the small numbers next to the channel number flash on the display.
- 3. Press the CHANNEL UP or CHANNEL DOWN button to begin scanning DCS privacy codes within the channel you selected.

The scan icon will continue to be displayed when DCS privacy code scan is ON. Your radio will continue

to scan DCS privacy codes and stop when an incoming transmission is detected. The radio will remain on that channel/privacy code for 10 seconds.

While setting DCS privacy code scan, if you do not press any buttons for 15 seconds, your radio will automatically return to LISTENING MODE on the channel/privacy code that was displayed before you entered more functions.

# During Scanning (While Receiving an Incoming Transmission). You Can Choose from the Following:

- a. Press and hold the TALK button to communicate on that channel/privacy code. Your radio will remain on that channel/privacy code and return to LISTENING MODE.
- b. Press the CHANNEL UP or CHANNEL DOWN button to resume scanning DCS privacy codes.

If you press the TALK button while scanning and not within 10 seconds of receiving a transmission, you will transmit on the channel/privacy code on which you lost received a transmission. This will return the radio to LISTENING MODE.

#### During Scanning (While Not Receiving an Incoming Transmission), You Can Choose from the Following:

- a. Press channel/privacy code that was displayed before you entered Mode Functions or channel/privacy code on which, during scanning, you last received a transmission. This will return the radio to the LISTENING MODE, Press and hold the TALK button to communicate on either the channel or channel MODF.
- b. Press the MODE button to proceed to next available Mode Function.
- c. Press the LOCK button to return to LISTENING MODE on either the channel or channel/privacy code that was displayed before you entered Mode Functions or the channel/privacy code on which, during scanning, you last received a transmission.







### **Set Call Tones**

You can choose between five (5) different call tones to transmit a unique call alert.

# To Change a Call Tone Setting:

- Press the MODE button until the letter "C" is displayed. The current cell tone number will be flashing on the display next to the "C." The current cell tone will sound for one (1) second.
- $2. \ Press\ CHANNEL\ UP\ or\ CHANNEL\ DOWN\ button\ to\ hear\ the\ other\ call\ tone\ settings.$
- 3. When you have selected a call tone choose one of the following:
  - a. Press the MODE button to enter the new setting and proceed to other functions.
  - b. Press the LOCK button to enter the new setting and return to LISTENING MODE.

NOTE: If no button is pushed for 15 seconds, the call tone setting will be set to the present selection.







# "Roger Beep" Confirmation Tone

Your listener will hear an audible tone when you release the TALK button. This alerts the other party that you have finished talking and that it is OK for them to speak. This feature can be turned On or Off.

# To Turn "Roger Beep" On or Off:

When you turn On your microTALK® radio for the first time, "Roger Beep" will be On



- 1. Press and release the MODE button until the "Roger Beep" icon flashes on the display. The current On or Off setting is displayed.
- 2. Press the CHANNEL UP or CHANNEL DOWN button to select "Roger Beep" On or Off.
- 3. When your desired Roger Beep Mode setting is displayed, choose one of the following:
- a. Press the MODE button to enter the new setting and return to LISTENING MODE.
- b. Press the LOCK button to enter the new setting and return to LISTENING MODE.
- c. Do not press any buttons for 15 seconds to enter the new setting and return to LISTENING MODE.

The setting you select will be saved when you turn your radio off and on again. When the "Roger Beep" is On, the "Roger Beep" icon will be displayed.

# **Declaration of Conformity**

This declaration is the responsibility of the manufacturer/importer

Cobra Electronics Europe Limited

Dungar House Northumberland Avenue

Dun Laoghaire County Dublin, Ireland

Date: 15 January 2007

This certifies that the following designated product

#### PRIVATE MOBILE RADIO: MT 600

complies with the essential protection requirements of R & TTE Directive 1999/5/EC on the approximation of the laws of the Member States relating to Radio Spectrum Matters: FMC and Flertrical Safety

This declaration applies to all specimens manufactured in accordance with the attached technical documentation described in Annex II of the Directive which forms part of this declaration.

Assessment of compliance of the product (class 2.6) with the requirements relating to the essential requirements according to Article 3 R & TTE was based on Annex IV of Directive 1999/5/EC and the following standards:

EN 50392 (2004-02)

Radio Spectrum: EN 300 296-1 V1.1.1 (2001-03) EN 300 296-2 V1.1.1 (2001-03) EMC: EN 301 489-1 V1.5.1 (2004-11)

EN 301 489-5 V1.3.1 (2002-08) Electrical Safety: EN 60950-1:2001 + A11:2004

DUBLIN. IRELAND MIKE KAVANAGH

RF Exposure:



### **Warranty & Customer Service**

For warranty and customer service information,

# C€0682⊕

For use in EU countries, subject to local laws and regulations.

CEEL® is a registered trademark of Cobra Electronics Europe, Ltd.

Snake design and microTALK® are registered trademarks of Cohra Flectronics Cornoration, USA

©2007 Cobra Electronics Europe Limited Dungar House, Northumberland Avenue Dun Laoghaire, County Dublin, Ireland

www.cobra.com



This equipment is intended for use in:													
AT	1	DE	/	GB	1	IT		MK	/	RO	1	l	
BA	1	DK	/	GR	1	LT	/	MT	>	RS		l	
BE	1	EE	7	HR	1	LV	7	NL	/	SE	1	l	
BG	1	ES	1	HU	1	Ш	1	NO	/	SI	1	l	
CH	1	FI	/	ΙE	/	LU	/	PL	\	SK	1	l	
CY	1	FR	/	IS	1	ME		PT	/	TR	1	l	
C7	/	/Countries of use											