MITEL 5310 IP CONFERENCE UNIT

FULL-DUPLEX CONFERENCING UNIT

Mitel[®] 5310 IP Conference Unit is a full-duplex IP conferencing unit that supports natural conversation while eliminating background noise – even in large meeting rooms – for exceptional voice quality and clarity. Highly intuitive to use, the 5310 IP Conference Unit connects to a range of Mitel IP phones, giving users access to familiar telephony controls.

VOICE QUALITY CONFERENCING

The 5310 IP Conference Unit uses beam-forming array technology to focus a microphone beam on the individual speaking, virtually eliminating all ambient room noise and side conversations. It can also be set to presentation mode, which focuses the microphone beam exclusively on one key speaker, allowing parties on the receiving end of a presentation to follow without distractions. Full-duplex operation supports natural conversation in either mode, allowing a conference user to enter a conversation without cutting off another speaker. Built-in noise reduction and automatic gain control further support quality voice conferencing. The 5310 IP Conference Unit is designed for meeting rooms up to 20' x 30' (6.1 m x 9.1 m) in size.

FULL FUNCTIONALITY, SINGLE CONNECTION

The 5310 IP Conference Unit saucer installs in seconds, plugging into the Conference Module on the Mitel 5324, 5330, 5330e, 5340, 5340e, and 5360 IP Phones for full conferencing and telephony functionality while eliminating the need for an additional LAN port. It is compatible with Mitel Communications Director (MCD), Mitel SX-200 IP Communications Platform (ICP), and the Mitel 5000 Communications Platform (CP).

MULTIMEDIA CAPABILITIES

The 5310 IP Conference Unit supports multimedia capabilities through Mitel Collaboration Advanced (MCA). With MCA, users can initiate instant collaboration sessions in an audio-, video- or web-based format, freely switching between multiple media.

FEATURES

- · Full-duplex handsfree operation
- Acoustic beam-forming technology to focus on lead speaker and eliminate background noise, side
- conversations etc. • Noise reduction
- · Automatic gain technology eliminates disturbing background noises when participants are moving around the room
- Integrated LED direction indicators that provide conference participants visual confirmation that the unit is receiving their voice
- · Dual-colored LEDs (orange / green) indicate status: mute, presentation mode, and directionality of microphone
- · Full telephony functionality through Mitel IP phones
- Presentation mode allows the user to focus / freeze the beam in a particular direction
- 5324, 5330, 5330e, 5340, 5340e, and 5360 IP Phones: conference controller application on the phones features softkey functionality for conference unit on / off, volume controls, presentation mode and mute
- Optional remote control mouse performs the functions of on, off, mute, volume up / down and presentation mode



RECOMMENDED CONFERENCE AREA

Designed for optimal use in offices or meeting rooms up to $20' \times 30'$ or 600 sq ft (6.1 m x 9.1 m or 55.5 m²).

AUDIO SPECIFICATIONS

| Frequency Range: | 300 Hz to 3500 Hz | | |
|------------------|---|--|--|
| Volume: | Peak sound pressure: 89 dB | | |
| | (at 1.6' or 0.5 meters) | | |
| Microphone: | 6 Microphones at 60° beams = 360° | | |
| | microphone coverage | | |

COMPRESSION SUPPORT

G.711, G.729

VOICE QOS

Supports IEEE 802.1p/q for quality of service.

POWERING OPTIONS

IEEE 802.3af Power over Ethernet (PoE).

Optional external universal AC power supply:

110 V 60 Hz AC / 220 V 50 Hz AC

 \cdot 5324, 5330, 5330e, 5340, 5340e, and 5360 IP Phones:

- Powered over Ethernet with a power source compliant to IEEE 802.3af
- 48 V DC Ethernet power adapter available, purchased separately (if required)

POWER CONSUMPTION

5 W (in addition to the power consumed by the phone that the 5310 IP Conference Unit is attached to).

ENVIRONMENTAL CONDITIONS

| | Temperature | Humidity |
|-------------|---------------|-------------|
| Operational | +4°C - +49°C | 34% at 49°C |
| | | 95% at 29°C |
| Storage | -40°C - +66°C | 15% at 66°C |
| | | 95% at 29°C |

PHYSICAL DIMENSIONS

| | Size (L x W x H) | Weight | |
|------------|---------------------------------|---------------------|--|
| Phone only | 10.5" x 4" x 3.5" | 1.35 lbs or 0.61 kg | |
| | (26.7 cm x 10.2 cm x 8.9 cm) | | |
| Packaged | 11.7" x 6.4" x 3.2" | 2.24 lbs or 1.02 kg | |
| | (29.6 cm x 16.2 cm x 8.1 cm) | | |

REGULATORY STANDARDS

EMC Canada: ICES-003 (Class B) USA: CFR Title 47, Part 15 (Class B) EU: EN55024 (EU), EN55022 (Class B) Australia / New Zealand: AS / NZS CISPR 22 Brazil: Resolution No. 442 / 2006 China: GB9254 Safety Canada: CSA C22.2 No. 60950-1 USA: UL 60950 EU: EN 60950, EN 60950-1 Australia / New Zealand: AS / NZS 60950-1 Brazil: Resolution 238 / 2000 China: GB4943 Telecom Canada: CS03 Part V (hearing aid compatible) USA: FCC part 68 (CFR 47) (hearing aid compatible) Australia / New Zealand: PTC220 AS / ACIS, S004

SYSTEM REQUIREMENTS

- Mitel Communications Director (MCD) Release 5.0 or later
- Mitel 5000 Communications Platform (CP) Release 5.1 or later
- \cdot Mitel SX-200 ICP Release 5.0 or later
- · Mitel SIP phones Release 8.0

SUPPORTED IP PHONES

- \cdot 5324 IP Phone
- \cdot 5330 IP Phone
- \cdot 5330e IP Phone
- \cdot 5340 IP Phone
- \cdot 5340e IP Phone
- \cdot 5360 IP Phone

MITEL | SIMPLY COMMUNICATING®

| GLOBAL HEADQUARTERS | U.S. | EMEA | CALA | ASIA PACIFIC |
|-----------------------|-----------------------|------------------------|-----------------------|-------------------------|
| Tel: +1(613) 592-2122 | Tel: +1(480) 961-9000 | Tel: +44(0)1291-430000 | Tel: +1(613) 592-2122 | Tel: +61(0) 2 9023 9500 |
| Fax: +1(613) 592-4784 | Fax: +1(480) 961-1370 | Fax: +44(0)1291-430400 | Fax: +1(613) 592-7825 | Fax: +61(0) 2 9023 9501 |

FOR MORE INFORMATION ON OUR WORLDWIDE OFFICE LOCATIONS, VISIT OUR WEBSITE AT MITEL.COM/OFFICES

mitel.com

MITEL

THIS DOCUMENT IS PROVIDED TO YOU FOR INFORMATIONAL PURPOSES ONLY. The information furnished in this document, believed by Mitel to be accurate as of the date of its publication, is subject to change without notice. Mitel assumes no responsibility for any errors or omissions in this document and shall have no obligation to you as a result of having made this document available to you or based upon the information it contains.

M MITEL (design) is a registered trademark of Mitel Networks Corporation. All other products and services are the registered trademarks of their respective holders.

© Copyright 2012, Mitel Networks Corporation. All Rights Reserved.