

Features:

- Caller ID display, supports FSK and DTMF
- Hearing aid compatible handset
- Data port
- Service buttons
- \bullet Press $\begin{tabular}{c} \bullet \end{tabular}$ or $\begin{tabular}{c} \bullet \end{tabular}$ to adjust the speaker and handset
- Default 600ms hook switch flash. Can be set from 100ms to 1000ms according to the network specifications.
- Redials the last number dialled and dialled number disappears within 5 minutes.

- PROG button
- Mute button
- R button Signalling the PBX to activate the flash function. The default is 600ms.
- Speaker button with indicator
- Message waiting indicator
- Busy tone disconnects automatically
- Programme service button with R.P master cloner and handheld cloner.
- Pre-dial function
- Desktop and wall mounting

CONTROLS AND FUNCTIONAL KEYS

Description of the functional keys **Features**

MUTE R


- Microphone switch (handset)
- Signalling the PBX to activate the flash function. The default is 600ms
- **A V**

=(

×


#

- To lower or increase the speaker and handset volume
- PROG - For programming
- Flash button
- REDIAL - Redial button
 - For on hook dialling (speaker phone mode)
 - Key for special services
 - Key for special services



Base unit - front

- 1. LCD screen display
- 2. 8 functional keys
- 3. 12 numerical keys
- 4. Service buttons
- 5. Mute indicator (LED)
- 6. Message waiting indicator
- 7. Hands-free microphone



Base unit - rear

- 8. Telephone line jack
- 9. Data port
- 10. Handset cord jack
- 11. Holes for wall mounting

Material: ABS, PMMA.

Colours: Anthracite with silver coloured plates.

Approved standards: EN 55022 and EN 55024.