

ErisTerminal™ SIP Mid Range Feature Deskset

VSP726A

Do more business with the VSP726A deskset. This easy-to-install, cost-effective system features Power over Ethernet (PoE) support, Dual-port Gigabit Ethernet and auto-provisioning. Because it uses DECT technology, the VSP726A makes it easier than ever to add an inexpensive cordless option. With the touch of a button, you can pair a handset (VSP601A) and/or headset (VSP 500A) to take calls away from your desk. Plus, you'll save time and money with local call recording using the built-in micro SD card slot, which allows you to record and review calls—without a subscription to your service provider. Managing multiple calls has never been easier thanks to advanced call handling features and support for up to four SIP lines/accounts. Support for the G.722 wideband codec for HD Audio means you'll enjoy superior voice quality too.



VSP726A Key Features

Advanced call handling.

Impress customers with comprehensive call handling features that are compatible with hosted and open-source PBX platforms.*

Flexibility.

With support for up to four SIP lines/accounts, you can manage multiple calls with advanced call handling features.

Intuitive design.

You're in business with a user-friendly interface, large backlit display, navigational pad and three soft keys.

One-button call routing.

Program up to 12 dual-function feature keys for convenient access, including shared call appearances (SCA), busy lamp (BLF), quick dial and feature codes.

Full-duplex speakerphone.

Finally, a speakerphone that can keep up with your calls. Increase participation by allowing parties on both ends to speak and be heard—at the same time—for conversations that are more true to life.

HD voice quality.

With G.722 wideband codec support for HD audio, calls have never sounded so rich and life-like.

Cordless convenience.

Thanks to the built-in DECT radio, you can pair a compatible VTech cordless headset and/or handset for hands-free mobility and super-clear sound quality.

Call recording with micro SD card slot.

Save calls right to your deskset using a micro SD card (sold separately) in the built-in port. Then enjoy free, easy access to recordings you can review later for missed details or quality assurance.

Dual-port Gigabit Ethernet.

Built-in support to enable seamless migration to GigE-based network infrastructure.

Power over Ethernet (PoE).

With PoE support, you can locate the phones anywhere that's convenient—no AC outlets or complicated wiring required.

Installation and Provisioning.

Integrated IEEE 802.3at PoE enables efficient deployment. Supports FTP, TFTP, HTTP, and HTTPS protocols for file provisioning. Model is configured by default to use Trivial File Transfer Protocol (TFTP), supports AES encrypted configuration file.

Three-year warranty.

Enjoy the peace of mind that comes with an industry-leading, standard three-year warranty.

Optional Accessories



DECT SIP Cordless Handset
VSP601A



DECT SIP Cordless Headset
VSP500A



*Compatible with Broadsoft® and Asterisk-based platforms.

Specifications, Weights and Dimensions

- Colour: GM (Charcoal)
- UPC: 735078036698
- Product dimensions (WxDxH):
BS: 182mm x 218mm x 51mm
Corded HS: 210mm x 51mm x 52mm
Corded HS on BS at 46 degree: 182mm x 197mm x 175mm
- Product weight: 0.91 kgs
- Giftbox dimensions (WxDxH):
186mm x 114mm x 223mm
- Giftbox weight: 1.14kgs
- Master pack dimensions (WxDxH):
389mm x 245mm x 241mm
- Master pack weight: 4.95kgs
- Quantity: 4

Interface

- DECT RF module embedded
- DECT (maximum register): 1 cordless headset VSP500A and/or 1 cordless headset VSP601A
- Micro SD card slot
- Dual Ethernet ports - GigE
- Base power: Class 3 Power over Ethernet (PoE) or optional AC adapter

Display, Keys and Indicators

- 158 x 57 pixels (w x h) LCD resolution
- LCD backlighting (white)
- 3 soft keys
- 10 dedicated feature keys
- 24 programmable feature keys (2 pages x12)
- 4-way navigational pad
- Message waiting LED indicator

Audio / Voice

- Full-duplex base speakerphone
- HAC receiver
- 2.5 mm corded headset jack
- HD Voice for receiver

Phone Features

- Supports up to 4 SIP account registrations
- Local phonebook up to 1000 entries
- Phonebook import/export
- LDAP/BroadSoft remote phonebook
- Call history up to 200 entries
- Shared Call Appearance (SCA)/Bridged-Line Appearance (BLA)
- Do Not Disturb (DND)

- Busy lamp fields (BLF)
- 3-way local conference
- N-way network conference
- Call barring/blocking (block anonymous/blacklist)
- Dial plan/digit map
- Hotline
- Intercom
- Mute
- Redial
- 10 speed dial entries
- Local call recording with micro SD card slot
- Call transfer: blind/attended
- Call hold
- Call park
- Call pickup
- Call forwarding: per-line basis (busy/always/no answer)
- Call restriction
- Call timer (call duration)
- Caller ID
- Call completion
- Phonebook matching (incoming and outgoing calls)
- Multicast paging
- Multi-language support
- Automatic Call Distribution (ACD)

Customisation

- Soft key configuration
- Programmable hard keys
- Custom startup and idle logo
- Web interface configuration (admin & user)
- Custom base ringer (.WAV)
- XML Browser
- Action URI
- Active URL (CTI support)
- Custom default file

SD Card Features

- Local call recording

Security

- 802.1x
- 802.1pq
- Phone lock - restricted config, calls and emergency call only
- Transport Layer Security (TLS)

- Mutual authentication (server and client)
- Certificate management (device & applications)
- AES encryption of config file for provisioning (128/64/32/16 bits)
- LLDP-MED

Network

- IPv4 or IPv6 with DHCP/Static/PPPoE
- STUN
- NAT
- RTP, SRTP
- SNTP
- VLAN
- DNS override
- Failover support and server redundancy
- Layer 3 QoS (ToS, Diffserv)

Voice Codec

- G.711 a-law & u-law
- G.722
- G.726
- G.729
- iLBC

Provisioning

- HTTP, HTTPS, FTP, TFTP
- DHCP options: 66, 159, 160
- TR-069
- PnP

Maintenance

- Diagnostic: pcap trace and port mirroring
- Software Update Over the Air (SUOTA)
- Schedule Resync - time and day setting
- Syslog

Compatibility

- BroadSoft® Broadworks
- Asterisk-based platforms

Other

- Optional AC adapter: VSP-ADPT02
- 3-year standard warranty

AC Adapter

- Colour: Black
- Product dimensions (WxDxH):
42.7mm x 49.2mm x 80.8 mm
- Product weight: 87.1g

Contact Us

VTech SIP Phones UK

 www.ukbusinessphones.vtech.com

 (0)1706 694070

 enquiries_ukbusinessphones@vtech.com

NOTE: Features and functionality may vary, depending on SIP service provider and/or SIP phone system platform.

© 2016 VTech Telecommunications Limited. All rights reserved. VTech® is a registered trademark of VTech Holdings Limited. ErisTerminal™ is a trademark of VTech.

