Yealink

Professional IP Phone Compatible with Microsoft® Skype for Business

The introduction of the T46G SFB desktop phone with Skype for Business firmware has been designed for executives and professionals and harnesses Optima HD Voice technology - delivering crystal-clear, lifelike conversations for users. Equipped with a modern Skype for Business interface, the user is met with familiar iconography and operation flows that reflects a true Skype for Business experience to minimize complexity and maximize productivity. The wireless "Better Together over Ethernet" (BToE) feature enables seamless switching between Skype for Business desktop-client and T46G SFB.

Designed with Microsoft® Skype for Business compatibility in mind, and loaded with premium features like conference, Boss/Admin and Outlook Calendar, the T46G SFB will raise your productivity to the next level.





Gigabit







lodern SFB UI

Support Bluetooth Earphone



Optima HD Audio

A seemingly magical combination of innovative software and hardware, coupled with wideband technology, deliver T46G SFB users an unparalleled acoustic performance. Advanced acoustic clarity technology- including full duplex, echo cancellation and adaptive jitter buffer - come together for an amazing face-to-face live experience.

Richer functionality

The T46G SFB is compatible with Skype for Business online, on-premises and hybrid deployment; effectively extending the benefits of Microsoft® SFB. The Skype for Business conference feature makes conference calls a breeze. The T46G SFB lets users synchronize Outlook Calendar meeting schedules in real-time by simply clicking to join a meeting. The T46G SFB is further outfitted with Directory synchronization, visual voicemail management, Boss/Admin and more- raising the bar for productivity to new heights.

Easy to use and easy to deploy

The modern Skype for Business interface provides for a rich visual presentation and easy menu navigation. Pin your favourite contacts directly to the home screen, arrange them however you'd like, and dial them easily with just a tap. Supporting Microsoft's Skype for Business Server in-band provisioning and in-band configuration management enables a carefree configuration and easier-than-ever mass deployment. Automatically deploy on a variety of servers- http, https, tftp and ftp.

Skype for Business



- 4.3" 480x272 pixel backlit colour screen
- Modern Skype for Business User Interface provides same experience as laptop version
- Intelligent Directory Search
- Synchronised Outlook Calendar with meeting "Join" feature
- Common Area Phone
- Boss/Admin support
- Dual-port Gigabit Ethernet
- PoE support
- Headset Electronic Hook Switch (EHS) support
- Built-in USB port, supports Bluetooth headset (via USB dongle)
- 6 x Expansion modules

Microsoft Partner

Exclusive Yealink UK LIFETIME WARRANTY



T46G SFB

Audio features

- Optima HD voice
- Full-duplex hands-free speakerphone with AEC
- Codecs: G.722 (Wideband), G.711 (A/ μ), G.723, G.729AB, G.726, GSM, iLBC
- DTMF: In-band, Out-of-band (RFC 2833) and SIP INFO
- VAD, CNG, AEC, PLC, AJB, AGC

Directory

- Contacts synchronize with client
- View SFB contacts and their current presence status
- Support local contacts
- Support Global search, Compatible with exchange
- Smart dialing
- Call history: placed/received/missed/forwarded

Signing into Microsoft SFB

- Sign in: PIN Authentication/User credentials
- Signing in via BToE
- Signing in via phone web interface
- · Auto root certificate fetch

BToE features

- Click to call/Click to answer
- Audio device switch from IP Phone to PC
- wireless paring with PC client
- As a PC Audio device

Interface

- Dual-port Gigabit Ethernet
- Built-in a USB port, support Bluetooth headset (Through USB Dongle)
- Power over Ethernet (IEEE 802.3af), class 0
- 1 x RJ9 (4P4C) handset port
- 1 x RJ9 (4P4C) headset port
- 1 x RJ12 (6P6C) EXT port :

Supports up to 6 expansion modules

Phone features

- Presence status synchronize with client
- · Reset presence status, Privacy mode
- · Phone Lock
- Favourite contacts sorting
- Favourite contacts click to call
- Call hold, call waiting, redial, mute
- Branch office support
- · Call forward, call transfer, call park
- SFB conferencing (Microsoft CCCP)
- Boss/Admin function
- Common Area Phone (CAP)
- Calendar function
- Support Group call pickup
- · Paging, Music on hold
- E911, Federation, Response group, Private line
- Ring tone selection/import/delete
- Visual voicemail, Message waiting indicator (MWI)
- · Volume adjustment

Display and indicator

- 4.3" 480 x 272-pixel color screen with backlight
- · Modern Skype for Business interface
- LED for call and message waiting indication
- · National language selection
- Caller ID with name, number, picture
- Presence status control: available, busy, DND, be right back, off work, appear away

Network and security

- SIP v1 (RFC2543), v2 (RFC3261)
- IPv4/IPv6
- Proxy mode and peer-to-peer SIP link mode
- IP Assignment: Static/DHCP/PPPoE
- DNS Assignment: Static/DHCP
- HTTP/HTTPS web server
- Time and date synchronization using SNTP

- UDP/TCP/DNS-SRV (RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS, DSCP
- · SRTP for voice
- Transport Layer Security (TLS)
- EWS authentication
- HTTPS certificate manager
- Digest authentication using MD5/MD5-sess
- IEEE802.1X

Management

- Configuration: browser/phone/Auto provisioning
- Auto provisioning: RPS/In-band provisioning
- In-Band Configuration Management
- QoE (Monitoring Reports)
- Single identity (active directory)
- Media Bypass, Firewall Traversal
- Reset to factory, reboot
- Package tracing export, system log
- · Screenshot via URL
- Phone log click to upload
- View License status

Other physical features

- External universal AC adapter (optional): AC 100~240V input and DC 5V/2A Output
- Power consumption (PSU): 1.8~5.4W
- Power consumption (PoE): 2.1~8.0W
- Dimension (W*D*H*T): 244mm*213mm*185mm*54mm
- Operating humidity: 10~95%
- Storage temperature: -10~50°C

Package features

- Qty/CTN: 5 PCS
- N.W/CTN: 7.6 kg
- G.W/CTN: 8.4 kg
- Giftbox size: 274mm*255mm*128mm
- Carton Meas: 660mm*286mm*263mm

Certification

















